



Instructions for Slate table sets

Rocca Natural Slate Tables and Accessories

Taking inspiration from the Mediterranean, our exclusive Rocca range is the perfect accessory to dining al-fresco

Product and care information:

Construction/Materials:

- The metal base is made of galvanised powder coated steel.
- The table top is made of carefully selected hand cut slate tiles and outdoor quality grout mortar, which has undergone a special process to give maximum strength.
- A metal reinforcement structure and a combination of lightweight composite material make these tables strong but light.
- The bottom of the table top is finished with a cement layer and contains screw holes for base attachment.

Maintenance:

The table top is treated to avoid staining. We recommend initial treatment and repeating this treatment annually, using Cadix Natural Impregator.

If the powder coating of the metal base is scratched it is recommended that the damaged areas are immediately covered with an outdoor quality black metal paint to avoid corrosion. (a car touch-up paint can be used)

In the event of a tile coming loose it should be repositioned and fixed by using super glue and outdoor quality grey grout mortar.

Product guarantee:

We offer a 1 year guarantee on the table top surface and metal base, on structural faults, excluding corrosion as this may be related to the use of the product.

Rocca tables are produced with Natural Slate, which naturally contains mineral and iron deposits.

During the long lifetime of a Rocca Slate table corrosion spots may develop on the surface. You may like the effect of this natural reaction, but it can also be avoided or reduced using Cadix Natural Impregnator, which also protects the surface of the table against staining and livens up the colour. Treatment is recommended in regular intervals, depending on local weather conditions.

Special outdoor tile sealants may also be used, but may reduce the natural character of the slate surface. (a matt or natural finish is recommended)

Rusty spots can often be removed by fine sanding paper and soapy water. Keep the surface moist whilst sanding to avoid scratching.

For further information, please visit: www.cadix.co.uk